Installation Guide: Hi-Flo Inside Miter

What is the **Hi-Flo Inside Miter ?**

The **Hi-Flo Inside Miter** is an Inside Miter for use with any style Gutter Guards. The design handles the high water flow conditions that are caused by roof valleys. The Hi-Flo Inside Miter comes in gray aluminum frame with a stainless steel screen that matches the most Gutter Guard colors, fully assembled, and fits up to a 6 inch gutter.

2 Install Methods:

- ✓ **Fascia Mount –** Attaches securely to the back of the gutter, trim to fit installation to fit most gutters.
- ✓ **Under Shingle Mount** - Fits under the roof shingle, easy install, and does not void any roof warranty*

How it Works:

1. Miter slows the water down using the Raised Ridges built into the screen.
2. Miter ridges changes the direction of the water flow to increase the water going into the gutter.
3. Miter has a larger & stronger 16 mesh Stainless Steel screen to allow for faster water absorption.
4. The Raised Screen keeps debris lifted up to be blown off, while only water runs into gutter.

These features work together to make the Hi-Flo Inside Miter the best solution for inside miter miters.
Hi-Flo Inside Miter is easy to clean with either a brush or leaf blower if needed.

Installation Overview:

Step 1: Prepare area, trim edges to fit

Step 2: Under Shingle or Fascia Mount

Step 3: Install Gutter Guard on both sides

Install Notes:

Fascia Mount: Clean and seal gutters, place miter over gutter area and mark to trim to fit, leave 1/2" longer to allow bend up of rear screen in order to screw to fascia and secure, mount front of miter to gutter lip, install gutter guard on both sides.

Under Shingle Mount: Clean and seal gutters, gently lift roof and valley, cut corners on the miter, slide under the roof shingle and valley, mount front of miter to gutter lip, install gutter guard on both sides.

**when correctly installed*