

LeafDeflector Gutter Guard

Product Specifications

Class A Fire-Rated | WUI Compliant | ASTM E84 / ASTM E2768 | Designed and Assembled in the USA

Sizes	5 in and 6 in gutter models
Product width (actual)	6 in (fits 5 in gutters) - 7 in (fits 6 in gutters)
Section length	48 in
Packaging	100 ft box (25 sections of 48 in)
Screen	Raised LeafDeflector screen pattern, 304 stainless steel mesh
Mesh	24 mesh, 0.014 in wire diameter, approx 576 holes per sq in
Rails	Aluminum, 0.020 in (24 gauge), painted Colonial Gray
Weight	Approx 1.5 lb per 48 in section (0.375 lb per ft)
Shipping weight per box	25 lb (5 in model) - 28 lb (6 in model)
Mounting methods	Under-Shingle Mount or Fascia Mount (optional)
Fits	4.0 in to 7.0 in gutter inside widths; custom sizes available
Warranty	45-Year Product Warranty + No-Clog Gutter Guarantee
Wind resistance	110 mph
Flow rating	Handles up to 44 in of rainfall per hour
Snow load (downward)	Up to 45 lb per sq ft
Fire compliance	Class A; conforms to WUI and ASTM E84 / ASTM E2768 standards
Origin	Designed and Assembled in the USA

Accessory - High-Flow Inside Miter

Form	Pre-made L-shape, flush lip
Front width	6 in front width, left and right
Mesh	Extra Large 16 mesh (0.018 in wire, approx 256 holes per sq in)
Material	304 stainless steel with raised screen ridges
Packaging	Box of 25

Notes

Rated performance figures are from the manufacturer specification sheet. Code acceptance for a specific project is determined by the local building department (authority having jurisdiction).

Wholesale program and pricing are available to qualified trade partners at leafdeflector.com/distributors/.